
Aviation Antenna HX-CA7606A

Harxon
a BDStar company

HIGH PRECISION COMPACT GNSS ANTENNA FOR AVIATION



HIGH PHASE CENTER STABILITY

HX-CA7606A features a multi-point feeding deign to achieve greater phase center stability. It effectively improves measurement accuracy and provides better positioning solution.

TRACKING IN CHALLENGING ENVIRONMENTS

The ability to receive low elevation signals with high gain and wide beam width makes HX-CA7606A a suitable choice for tracking visible satellites and provide stable and precision GNSS data under different flight attitudes.

STRONG ANTI-INTERFERENCE PERFORMANCE

The antenna LNA features an excellent out-of-band rejection performance, which can suppress the electromagnetic magnetic interference, providing the stability and reliability of GNSS signals. Also it effectively avoids disconnection dangerous when receivers are being interfered by wireless communication systems, for example power grid, communication base station or radio modem applications.

SMALL SIZE WITH RUGGEDIZED STRUCTURE

The dimension of HX-CA7606A is only 115*71.8*27.4mm (without connector) with a light weight of 150 gram, which makes it ideal to be placed over the professional drones, unmanned vessels or where high precision operations are needed. The IP67 ruggedized cover can protect the antenna from dust and water, furthermore ensure long-time outdoor operation due to its patented waterproof and breathable design.

KEY FEATURES

- Support GPS, Glonass, Galileo, Beidou, QZSS and SBAS signal reception
- Stable phase center guarantees the accuracy of positioning within millimeter-level
- Strong anti-interference ability to endure the challenging operating environments
- Small form factor with IP67 ruggedized structure

GEOBOX®
www.geospb.ru
ООО "Геоприбор"
Россия, г. Санкт-Петербург
пр. Энгельса, дом 107, корпус 3
(812) 438-33-66, 943-43-25
8-800-200-99-82
e-mail: info@geobox.ru

ГЕОПРИБОР EST.2000

Aviation Antenna HX-CA7606A

Harxon a BDStar company

PERFORMANCE

Signal Received	
GPS	L1/L2
GLONASS	L1/L2
GALILEO	E1
BDS	B1/B2/B3
QZSS	L1/L2
SBAS	L1
Nominal Impedance	50Ω
Polarization	RHCP
Axial Ratio	≤3dB
Gain at Zenith (90°)	
1164-1278MHz	3dBi(maximum)
1520-1615MHz	4dBi(maximum)
LNA Gain	36dB(typical)
Noise Figure	≤2dB
Output/Input VSWR	≤2.0
Operation Voltage	+3.3VDC to +12VDC
Operation Current	45mA(maximum)
Group Delay Ripple	<5ns

MECHANICAL

Dimensions	115*71.8*41.9mm
Connector	TNC female
Weight	≤150g
Mounting	4 M4 screws installation

ENVIRONMENTAL


Temperature	
Operating	-40℃ to +85℃
Storage	-55℃ to +85℃
Humidity	95% non-condensing
Water/Dust Resistance	IP67
Regulatory Compliance	FCC CE RoHS REACH

For the most recent details of this product:
http://en.harxon.com/products-detail.php?ProId=151

en.harxon.com
sales@harxon.com
9/F, Block B, Building D3, TCL International E City, NO.1001 Zhongshanyuan Road, Nanshan District, Shenzhen, China
Tel: +86-755-26989948
Fax: +86-755-26989994

Version 2 Specifications subject to change without notice.
©2020 Harxon Corporation. All rights reserved.
Printed in China
December 2019

Structure& Phase Center Drawing (mm)



TOP VIEW SIDE VIEW BOTTOM VIEW

Undeclared tolerance:±0.3mm

GEOBOX® www.geospb.ru
ООО "Геоприбор"
Россия, г. Санкт-Петербург
пр. Энгельса, дом 107, корпус 3
(812) 438-33-66, 943-43-25
8-800-200-99-82
e-mail: info@geobox.ru